

# STANLEY®

## RECESSED LED PANEL LIGHT

### SXIM-P01 & P05



#### AVAILABLE WATTAGE OPTIONS:

- 12W
- 18W
- 24W

#### BENEFITS:

- Energy efficiency.
- Improved environmental performance.
- Ability to operate in cold conditions.
- No heat or UV emissions.
- Design flexibility.
- Instant lighting and the ability to withstand frequent switching.
- Long lifespan.
- General lighting for limited build-in height.

(CCT) Color Temperature Switch



# IP20

#### SPECIFICATIONS

Shape:	Round LED Lamp
Fitting:	Recessed Ceiling
Finish:	White

#### ADDITIONAL INFORMATION

Volt:	100-277V 50-60Hz
Beam Angle:	110°
Certification:	CE

#### AVAILABLE WATTAGE OPTIONS

Power	Tone	Brightness	Size	Dimmable / Non Dimmable	Model
12W	6000K	130Lm	170mm x 17mm	Non Dimmable	SXIM-P01-12W6K
18W	6000K	130Lm	220mm x 17mm	Non Dimmable	SXIM-P01-18W6K
12W	3000K, 4000K, 6500K	1000Lm	170mm x 17mm	Non Dimmable	SXIM-P05-R12WCCT
18W	3000K, 4000K, 6500K	1100Lm, 1200Lm, 1100Lm	220mm x 17mm	Non Dimmable	SXIM-P05-R18W-CCT
24W	3000K, 4000K, 6500K	1610Lm	280mm x 17mm	Non Dimmable	SXIM-P05-R24WCCT



## THE MEASURE OF A PRO™